



Sizes in cm

CE RoHS     (with Arne luminaire)

Code: ARP03 catenary attachment

Accessory allowing the luminaire to be affixed to a catenary using a simple fastening system.

Gracias a una rotación de 360° sobre su propio eje, facilita una distribución lumínica totalmente orientable en planta. Thanks to a 360° rotation on its own axis, allows an orientable on site lighting distribution. Metal wire range admissible: Ø 6-8 mm.

Materials: Stainless steel powder-coated finish bracket.

Powder-coated finish aluminium injection fastening parts. Black PA6 injection joints.

Stainless steel screws.

Finishes:



Light grey (RAL 9006)
(other colours available to order)



Dark grey (RAL 7024)

Size (cm): 31 x 11 x 4

Weight (kg): 0.8

Installation: Suitable for catenary attachment by means of a fastening accessory. The component is delivered disassembled.

The component can be combined with the Arne floodlight product range.

(For further information log onto the website urbidermis.com).

*Luminaire not included

*Catenary wire not included

For calculation in ground type II (according to UNE-40) and wind speed of 29 m/s, with soil formed by loose or wet dirt or sand of medium compactness ($E_0 = 4800 \text{ KN/m}^2$), with HM-20 concrete. Non-binding information. We advise to carry out checks for each situation.