



Sizes in cm



Poles manufactured in class 1 S-275 JR steel cylindrical tube, in one or two segments depending on the height.  
Hot-galvanised painted finish.

**Heights:**

One section (Ø 114,5mm): 3,6m / 4,4m / 5,2m  
Two sections (Ø 152mm / 114,5mm): 6,8m

**Affixing:**

By means of a base plate and bolts fastened to a foundation block.

**Spacing between bolts:**

(3,6m / 4,4m / 5,2m) 210x210 mm  
(6,8m) 300x300 mm

Bolts: (4x) M18x500 \*included

**Applicable standards:** EN 40, EN ISO 1461, EN 10025, EN 1090, ISO 12944

Code	Total height (m)	Visible height (m)	Outer pole diameter (mm)	Thickness (mm)	Base plate (mm)	Spacing between bolts (mm)	Bolts (x4)	Door	Foundation (xyz) (mm)	No. Luminaires accepted
TMF1P	3,6	3,4	114	3	300x300x10	210x210	M18x500	1	650x650x600	1/2
TMF21P/ TMF22P	4,4	4,2	114	3	300x300x10	210x210	M18x500	1	650x650x600	1/2
TMF31P/ TMF32P	5,2	5,0	114	3	300x300x10	210x210	M18x500	1	800x800x700	1/2
TMF41P	6,8	6,6	114/152	3	400x400x10	300x300	M18x500	2	900x900x700	1/3

For calculation in ground type II (according to UNE-40) and wind speed of 29 m/s, with soil formed by loose or wet dirt or sand of medium compactness ( $E_0 = 4800 \text{ KN/m}^2$ ), with HM-20 concrete. Non- binding information. We advise to carry out checks for each situation.