



Sizes in cm

CE RoHS     (with Arne luminaire)

Code: ARP03S symmetrical light attachment for catenary

Accessory allowing an indirect light luminaire to be affixed to a catenary using a simple fastening system. Along with the Arne floodlight for indirect lighting, it allows public areas to benefit from more pleasant lighting, bringing a light quality reminiscent of indoor spaces to the streets.

Materials: Metal wire range admissible: Ø 6-8 mm.

Mass white painted PIMC shade.

Paint finish steel structural tubes.

Paint finish aluminium top cover.

Powder-coated finish aluminium injection fastening parts.

Stainless steel screws.

Colours: light grey (RAL 9006).
(other colours available to order)

Size (cm): 62 x Ø80

Weight (kg): 9

Installation: Suitable for catenary attachment by means of a fastening accessory. The component is delivered disassembled in two parts: shade and structure. The component can be combined with the Arne floodlight product range for indirect lighting (for further information about Arne indirect lighting, log onto the website urbidermis.com)

*Luminaire not included

For calculation in ground type II (according to UNE-40) and wind speed of 29 m/s, with soil formed by loose or wet dirt or sand of medium compactness ($E_0 = 4800 \text{ KN/m}^2$), with HM-20 concrete. Non-binding information. We advise to carry out checks for each situation.