

Bancal Table

Julià Espinàs and Olga Tarrasó, 2012

CONCEIVED FOR PUBLIC SPACES WHERE ADEQUATE SURFACES ARE REQUIRED FOR LEISURE. CREATED TO COMPLEMENT THE BANCAL FAMILY.



- 1 | Optimal for parks and leisure spaces
- 2 | Designed for maximum accessibility
- 3 | Easy installation



Bancal table

The table is created to complement the Bancal family. It is conceived for public spaces where adequate surfaces are required for leisure. Like its predecessor, it is a simple and robust element which allows rectangular surfaces of

76x220 cm to be formed. It can be installed in an alignment or as independent units. Its components are separated into a top formed by five FSC tropical wood slats joined together by three

metal plates. The structure is formed by two legs and folded steel sheet crossbeam, which form a stable, easy to assemble and install element.

Materials and finishes

· Legs
Folded steel sheet structure with anti-rust production and powder-painted.

· Tropical wood slats with FSC certificate
Boards of solid tropical wood of 50x220mm length with FSC pure certificate, finished in oil in two components. The FSC certified tropical wood comes from Africa or Central America.
This wood is obtained complying with all the legal and environmental regulations of the country of origin, controlling the chain of custody, ensuring the sustainability of the woods and minimizing the environmental

impact. The wood does not come from primary forests. To protect the surface of the slats, we use an oil in two components. This is a dual-layer protection especially formulated for the long-lasting treatment of wooden elements for outdoors.
Its main attributes are:

- Conservation of the natural appearance and touch of the wood.
- Good penetration of the colour pigments thanks to nanotechnology.
- Long-lasting molecular action of the oil of the second layer.

- Powerful fungicide, breathable and water-repellent material.
- High protection against the effect of UVA rays and heat-resistant.
- Prevention against colour loss and surface scaling.
- Fast drying, ideal for industrial handling.
- It is an environment-friendly product, 100% free of volatile organic compounds and without isocyanate.

All the fastening bolts of the slats are in steel with anti-rust protection.

Maintenance

No functional maintenance is required except to preserve original wood colour.

Weight

90Kg.

Installation

It is fastened with two anti-rust treated steel bolts per leg introduced into holes previously drilled in the paving and filled with epoxy resin, fast-drying cement or similar. The table is delivered dismantled in two parts, the top and the two legs.
The table is delivered with the fastening bolts, the screws and the assembly instructions.

Model

Sizes in cm.

