

## Trapecio Bench

Antonio Montes, Montserrat Periel. 2003

SANTA & COLE  
urbidermis



CE

**Code:** TRB11, TRB version UHPC

**Materials:** Structural timber beams 4.50 m long with an approximate section of 20 x 40 cm made from glulam, protected with one-coat oil.

The supports are made of hot-dip galvanised shaped steel with painted finish, to which the two beams are fixed using steel screws with anti-rust protection.

UHPC version comprises two UHPC blocks, a material with very good structural performance and durability.

Both beams are 4.50 m long with a section of approximately 20 x 40 cm, and are mass coloured in earth, white or grey tones, with waterproof exposed aggregate finish.

**Slats:**

Glulam larch. One-coat oil finish

UHPC version:

Earth UHPC. Water repellent

Grey UHPC. Water repellent

**Structure:** Galvanised steel. Painted RAL 9006

(Other colours available to order)

**Weight (kg):**

380

UHPC version: 700

**Installation:** The bench is fixed using a concrete cube and stud anchor, 10 cm below the pavement surface.

The bench is delivered dismantled with assembly instructions. The screws and stud anchor are delivered with the supports.

**Maintenance:** Because of the properties of the material, no functional maintenance is required.

(For further information about this product, log onto the website [urbidermis.com](http://urbidermis.com))

**Applicable standards:** UNE EN 335, UNE EN 12727, UNE EN 581, ISO 12944, UNE 41510, UNE-EN ISO 7599, EN 338, NF B 50 100

UHPC version: UNE-EN 13369, UNE-EN 13198, UNE-EN 13369, UNE-EN 12390-3, UNE-EN 12504-1

